# liquid temperature calibration baths



### **Unheated Baths**

Designed to be used with a clip-on Tempette or Tempunit® thermoregulator, these baths incorporate carrying handles for added safety. All baths have stoved enameled steel outer cases and are supplied with bridge mounting plate to hold the thermoregulator.

Polypropylene spheres can be used to create a ball blanket so as to reduce evaporation and heat loss, whilst providing instant access to the bath.

## Four bath capacities – 8, 12, 18 and 26 litre

- Stainless steel construction
- Seam-free and corrosion resistant stainless steel inners for easy cleaning
- Rugged splash-proof case
- Integrated carrying handle
- Maximum working temperature of 200°C
- All models come with a 3 year warranty as standard

### 48 litre

- 48 litres capacity
- Welded construction
- All submerged parts are made from stainless steel
- Rugged splash-proof case
- Maximum working temperature of 200°C



**B-8** 

B-12

#### **Technical Specification**

Capacity litres		8	12	18	26	48
Dimensions (mm)	Length Width Height	265 325 172	354 325 172	530 325 172	530 325 222	594 365 298
Internal Dimensions (mm)	Length Width Height	240 300 150	329 300 150	505 300 150	505 300 200	559 330 274
Top of bath to liquid level max depth (mm)		65	65	65	65	65
Working length to thermoregulator (mm)		115	205	380	380	430
Working depth - max/min (mm)		130/100	130/100	130/100	180/150	255/224
Working capacity - max/min (litres)		8.0/6.0	11.6/8.4	18.0/13.2	26.0/20.5	48.5/42.5

For temperatures up to 250  $^{\circ}\text{C}$  we recommend the use of the LCB range of baths.

#### **Ordering Information**

Product Code	Description				
FBATH08 FBATH12	B-8 stainless steel bath, 8 litre capacity B-12 stainless steel bath, 12 litre capacity				
FBATH18	B-18 stainless steel bath, 18 litre capacity				
FBATH48	B-26 stainless steel bath, 26 litre capacity B-48 stainless steel bath, 48 litre capacity				



